

IN THE CLAIMS

Please amend the claims as follows:

1. *(previously presented)* A method of transmitting signals from a plurality of base stations (4; 10, 12) to the same mobile station (6; 18) in handoff, said method comprising the steps of:

transmitting first signals comprising a first communication and first associated information from one base station (4; 10) of said plurality of base stations to said mobile station;

transmitting second signals comprising said first communication, a second communication and second associated information, said second associated information differing at least partially from said first associated information, from another base station (4; 12) of said plurality of base stations to said mobile station; wherein said second communication is only transmitted from said another base station of said plurality of base stations; and

receiving at said mobile station said first and second signals, wherein said mobile station processes said first and second signals in accordance with the first and second associated information.

2. *(original)* A method as claimed in claim 1, wherein said first communication comprises speech.

3. *(original)* A method as claimed in claim 1, wherein said first communication comprises signalling information only.

4. *(previously presented)* A method as claimed in claim 1, wherein said first communication is provided on dedicated channels.

5. *(previously presented)* A method as claimed in claim 1, wherein said second communication is data.
6. *(previously presented)* A method as claimed in claim 1, wherein said second communication is provided in a shared channel.
7. *(currently amended)* A method as claimed in claim 1, wherein said first and/or said second associated information comprise information on ~~[[the]]~~ a rate concerning interleaving of speech and data of the respective first and second signals.
8. *(previously presented)* A method as claimed in claim 1, wherein said first and/or said second associated information comprise at least one code word.
9. *(previously presented)* A method as claimed in claim 1, wherein said first and/or said second associated information comprises first information associated with the first communication and second information associated with the second communication.
10. *(currently amended)* A method as claimed in claim 1, wherein first and second associated information comprise the same information ~~[[in]]~~ with respect ~~[[of]]~~ to the first communication.
11. *(cancelled)*
12. *(cancelled)*
13. *(currently amended)* A method as claimed in claim 1, wherein said ~~first and second~~ base and said mobile stations communicate using ~~[[the]]~~ a code division multiple access technique.

14. *(original)* A method as claimed in claim 13 wherein said first and second communications use different spreading codes.

15. *(currently amended)* A method as claimed in claim 1, wherein at least two of said ~~first~~ base stations are connected to different control elements, said control elements defining the first and/or second associated information.

16. *(original)* A method as claimed in claim 15, wherein said elements comprise radio network controllers.

17. *(previously presented)* A network comprising a plurality of first stations and a plurality of second stations, each of said first stations being connected to a control element, wherein at least one of said first stations is connected to one control element and at least one of the first stations being connected to a different control element, wherein, in a first mode, when a second station is in communication on a dedicated channel with a plurality of first stations controlled by the same control element the first stations transmit identical control information to said second station and, in a second mode, when a second station is in communication on a shared channel with a plurality of first stations which are controlled by a plurality of different control elements, the control information transmitted by said first stations to said second station is differently coded.

18. *(previously presented)* A network as claimed in claim 17, wherein said control information being used by said second station in said first and second modes is to control the processing carried out by the second station in respect of signals received from said plurality of first stations.

19. *(previously presented)* A network as claimed in claim 17, wherein said control information is in accordance with a first coding in the first mode and in accordance with a second coding in the second mode.

20. *(previously presented)* A network as claimed in claim 19, wherein said first coding has a first number of symbols available using a first number of bits and said second coding has a second number of symbols available using a second number of bits, wherein said first number of symbols is greater than said second number of symbols.

21. *(previously presented)* A network as claimed in claim 17, wherein the control information comprises a first number of code words in the first mode and a second number of code words in the second mode, said first number of code words being less than said second number of code words.

22. *(original)* A network as claimed in claim 21, wherein the number of bits defining the or each code word in the first mode is different to that of the or each code word in the second mode.

23. *(currently amended)* A method of transmitting signals from a plurality of first stations to the same second station, said method comprising the steps of:

transmitting first signals including first associated information on a dedicated channel from one of said plurality of first stations to said second station;

transmitting second signals including second associated information on a shared channel, differing at least partially ~~on a shared channel~~ from said first associated information from another of said plurality of first stations to said second station, said second signals at least partially differing from said first signals by the coding thereof; and

receiving at said second station said first and second signals, wherein said second station processes said first and second signals in accordance with the first and second associated information.

24. *(withdrawn)* A mobile terminal comprising:

receiving means for receiving first signals from one of a plurality of base stations and second signals from another of said plurality of base stations, said first signals comprising a first

communication and a first associated information, and said second signals comprising said first communication, a second communication and second associated information; wherein said second communication is only received from said another of said plurality of base stations; and

processing means arranged to process said first and second signals in accordance with the first and second associated information.